

IN THE CLAIMS

Please amend the claims as follows:

Claim 1 (Currently Amended): A disk apparatus for reproducing a disk on which information is recorded by pits or marks with various lengths, comprising:

a photodetection unit configured to divisionally detect light reflected by the disk as a plurality of photodetection signals; and

a tracking error signal generation unit configured to generate a tracking error signal on the basis of a phase difference between the plurality of photo-detection signals detected by the photodetection unit, wherein

the tracking error signal generation unit includes[[:]] an equalization unit configured to equalize waveforms of the plurality of photodetection signals detected by the photodetection unit, ~~and~~

the equalization unit has first frequency-gain characteristics that obtain a maximum gain of not less than 15 dB at a frequency corresponding to a shortest pit or mark, and second frequency-gain characteristics in which a gain attenuates within a frequency band not less than the frequency corresponding to the shortest pit or mark, and

the equalization unit has third frequency-gain characteristics that obtain a gain of not more than -3 dB at a frequency three times the frequency corresponding to the shortest pit or mark.

Claim 2 (Canceled).

Claim 3 (Original): An apparatus according to claim 1, wherein the equalization unit includes:

a high-pass filter having frequency-gain characteristics in which a gain is constant within a first frequency range not more than a first frequency, a gain is constant within a second frequency range not less than a second frequency which is more than the first frequency, and a gain increases in a third frequency band between the first and second frequencies, and

a low-pass filter having frequency-gain characteristics in which a gain attenuates within a fourth frequency band not less than a third frequency.

Claim 4 (Canceled).

Claim 5 (Currently Amended): An apparatus according to claim ~~[[4]]~~ 3, wherein the first frequency range is ~~a frequency range~~ set from 0.5 to 1.5 times a frequency corresponding to a pit or mark with which a reproduction signal amplitude saturates,

the second frequency range is ~~a frequency range~~ set from 0.5 to 1.5 times the frequency corresponding to the shortest pit or mark,

the third frequency matches the frequency corresponding to the shortest pit or mark, and

a Q value of the low-pass filter is not less than 2.

Claim 6 (Currently Amended): An apparatus according to claim 1, wherein a transfer function H of the equalization unit is given by:

$$H = (1 + 3.99 \times 10^{-8}s) / (1 + 1.58 \times 10^{-8}s + 1.41 \times 10^{-16}s^2 + 1.24 \times 10^{-24}s^3)$$
$$s = j\omega \text{ (complex frequency)}$$

Claim 7 (Original): An apparatus according to claim 5, wherein a ratio of the shortest pit or mark to the pit or mark for which the reproduction signal amplitude saturates is 2 : 8.

Claim 8 (Original): An apparatus according to claim 1, wherein the gain at the frequency corresponding to the shortest pit or mark is not less than 0.

Claim 9 (Currently Amended): An information processing method for processing a signal read out from a disk on which information is recorded by pits or marks with various lengths, comprising:

divisionally detecting light reflected by the disk as a plurality of photodetection signals;

equalizing waveforms of the plurality of detected photodetection signals by an equalizer having first frequency-gain characteristics that obtain a maximum gain of not less than 15 dB at a frequency corresponding to a shortest pit or mark, and second frequency-gain characteristics in which a gain attenuates within a frequency band not less than the frequency corresponding to the shortest pit or mark; and

generating a tracking error signal on the basis of a phase difference between the plurality of equalized signals, wherein

the equalizer has third frequency-gain characteristics that obtain a gain of not more than -3 dB at a frequency three times the frequency corresponding to the shortest pit or mark.

Claim 10 (Canceled).

Claim 11 (Original): A method according to claim 9, wherein the equalizer includes:

a high-pass filter having frequency-gain characteristics in which a gain is constant within a first frequency range not more than a first frequency, a gain is constant within a second frequency range not less than a second frequency which is more than the first frequency, and a gain increases in a third frequency band between the first and second frequencies, and

a low-pass filter having frequency-gain characteristics in which a gain attenuates within a fourth frequency band not less than a third frequency.

Claim 12 (Canceled).

Claim 13 (Currently Amended): A method according to claim ~~[[12]]~~ 11, wherein the first frequency range is ~~a frequency range set from~~ 0.5 to 1.5 times a frequency corresponding to a pit or mark with which a reproduction signal amplitude saturates,

the second frequency range is ~~a frequency range set from~~ 0.5 to 1.5 times the frequency corresponding to the shortest pit or mark,

the third frequency matches the frequency corresponding to the shortest pit or mark,  
and

a Q value of the low-pass filter is not less than 2.

Claim 14 (Currently Amended): A method according to claim 9, wherein a transfer function H of the equalizer is given by:

$$H = (1 + 3.99 \times 10^{-8}s) / (1 + 1.58 \times 10^{-8}s + 1.41 \times 10^{-16}s^2 + 1.24 \times 10^{-24}s^3)$$

$s = j\omega$  (complex frequency).

Claim 15 (Original): A method according to claim 13, wherein a ratio of the shortest pit or mark to the pit or mark for which the reproduction signal amplitude saturates is 2 : 8.

Claim 16 (Original): A method according to claim 9, wherein the gain at the frequency corresponding to the shortest pit or mark is not less than 0.